



GLOBESTAR WT UNIVERSAL

MATERIAL HANDLING TIRES

GLOBESTAR WT One of the Widest Solid Tires

A universal solid tire, **GLOBESTAR Wide-Tread** ensures consistency in performance and durability. It is one of the widest tires in the industry.





ENERGY SAVING Very good energy saving due to very low rolling resistance.



OPERATING TIME Very good operating time due to low heat build-up and low cost per hour.



LIFE TIME

Ideal tire life and reduced maintenance cost.



CORNERING STABILITY

The wide tread provides very good cornering stability and driver comfort.









BEAD WIRES

TREAD COMPOUND

BASE COMPOUND

Tire Size	Rim Size	Clip on	Tire Dimensions		Tire Dimensions		Other Vehicles Load Capacity (Kg)		Tire load capacity on forklifts at Max. Speed			
									16 Miles/h (Lbs)		25 Km/h (Kg)	
			Max width ±1% (mm)	OD ± 2% (mm)	Max width ±1% (inch)	OD ± 2% (Inch)	6 Km/h	10 Km/h	Load wheel	Steer wheel	Load wheel	Steer wheel
4.00-4	2.10 -4		97	304	3.82	11.97	535	485	1180	910	535	412
4.00-4	2.50 C-4		97	304	3.82	11.97	535	485	1180	910	535	412
4.00-8	3.00 D-8	•	104	403	4.09	15.87	950	860	2095	1610	950	730
5.00-8	3.00 D-8	•	115	444	4.53	17.48	1415	1285	3120	2405	1415	1090
15x4 1/2-8 125/75-8	3.00 D-8	•	115	374	4.53	14.72	1040	945	2295	1765	1040	800
16x6-8 150/75-8	4.33 R-8	•	138	406	5.43	15.98	1455	1360	3210	2535	1455	1150
18x7-8 180/70-8	4.33 R-8	•	152	451	5.98	17.76	2145	1945	4730	3640	2145	1650
140/55-9	4.00 E-9	•	129	377	5.08	14.84	1170	1060	2580	1986	1170	900
6.00-9	4.00 E-9	•	139	517	5.47	20.35	1885	1710	4155	3195	1885	1450
21x8-9 200/75-9	6.00 E-9	•	179	514	7.05	20.24	2755	2505	6075	4675	2755	2120
6.50-10	5.00 F-10	•	156	563	6.14	22.17	2340	2125	5160	3970	2340	1800
200/50-10	6.50 F-10	•	191	455	7.52	17.91	2470	2240	5445	4190	2470	1900
23x9-10 225/75-10	6.50 F-10	•	197	580	7.76	22.83	3445	3125	7595	5840	3445	2650
7.00-12	5.00 S-12	•	167	645	6.57	25.39	2920	2645	6435	4940	2920	2240
23x10-12 250/60-12	8.00 G-12	•	232	580	9.13	22.83	3770	3420	8310	6390	3770	2900
27x10-12 250/75-12	8.00 G-12	•	243	670	9.57	26.38	3900	3540	8600	6615	3900	3000
7.00-15	5.50-15	•	174	704	6.85	27.72	3545	3215	7815	6005	3545	2725
7.00-15	6.00-15	•	174	704	6.85	27.72	3545	3215	7815	6005	3545	2725
8.15-15 (28x9-15) 225/75-15	7.00-15	•	214	680	8.43	26.77	3770	3420	8310	6390	3770	2900
8.25-15	5.50-15	•	209	806	8.23	31.73	4750	4300	10470	8045	4750	3650
8.25-15	6.50-15	•	209	806	8.23	31.73	4750	4300	10470	8045	4750	3650
250-15 250/70-15	7.00-15	•	216	709	8.50	27.91	4750	4310	10470	8045	4750	3650
250-15 250/70-15	7.50-15	•	216	709	8.50	27.91	4750	4310	10470	8045	4750	3650
300-15 315/70-15	8.00-15	•	262	811	10.31	31.93	5850	5310	12895	9920	5850	4500
355/65-15	9.75-15	•	290	819	11.42	32.24	7800	6430	17190	13230	7800	6000
9.00-20	6.50-20		231	970	9.09	38.19	5340	5200	11770	9810	5340	4450
9.00-20	7.00-20		231	970	9.09	38.19	5340	5200	11770	9810	5340	4450
10.00-20	7.00-20		248	1005	9.76	39.57	6000	5450	13230	11025	6000	5000
10.00-20	7.50-20		248	1005	9.76	39.57	6000	5450	13230	11025	6000	5000
10.00-20	7.50-20	•	248	1005	9.76	39.57	6000	5450	13230	11025	6000	5000
10.00-20	8.00-20		248	1005	9.76	39.57	6000	5450	13230	11025	6000	5000
12.00-20	7.50-20		284	1084	11.18	42.68	7500	6810	16535	13780	7500	6250
12.00-20	8.00-20		284	1084	11.18	42.68	7500	6810	16535	13780	7500	6250
12.00-20	8.50-20		284	1084	11.18	42.68	7500	6810	16535	13780	7500	6250





GRI takes a long-term view, looking beyond the obvious horizon. The **GREEN X CIRCLE** is a global farmer ecosystem connecting natural rubber farmers with crop farmers worldwide focusing on sustainable farming practices to increase productivity that will benefit farming communities and inspire greatness for generations to come.



GRI produces high-grade specialty tires that are built sustainably using pure natural rubber in Sri Lanka. Founded in 2002, the company produces material handling solid tires, radial agriculture tires and construction tires. GRI has operations in 9 countries, and a business presence in more than 50 countries. In 2018, GRI opened an advanced manufacturing plant in Sri Lanka to produce radial agricultural tires. In 2020, GRI commenced construction of a large mixing facility for tire compounds and in 2021 began further expansion of its advanced specialty tire plant. GRI ensures its commitment to sustainability and environmental protection through all its strategies and processes. Environmentally sustainable growth is our strategic goal, both now and for generations to come.

> info@gritires.com www.gritires.com

(f) www.facebook.com/GRItires/ (@) www.instagram.com/gritires/?hl=en

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd are covered by limited warranty, which includes cover against material, workmanship and other manufacturing defects subject to the usage of the tires under specified conditions. If any tire covered by this warranty is deemed unserviceable due to aforementioned defects, we will either repair the tire or provide an allowance to purchase a new tire at the current price as a percentage of the worn off tread of the original tire at the time of making the claim.

The cost of transportation, service and paid sales tax will be borne by the owner of the claimed tire. The limited warranty is exclusively applicable to the tire owner who is using the product. No other warranty of liability, expressed or implied, is applicable to the limited warranty or to our products.