

Long
runtime

Increased
farm productivity

Reinforced
and durable sidewall

Lowered
tire pressure



F77

HEAVY DUTY

RADIAL FLOTATION TIRE

A technologically advanced radial flotation tire for tractors, harvesters, grain carts and farm implements developed to carry heavy loads on demanding terrain conditions. The Multi-directional tread pattern and wide tread width ensures superior flotation suitable for 50/50 ON/OFF road application and provides high traction and stability. The F77's tire construction and extended wear compounds ensure enhanced tire life, higher load carrying capacity and improved puncture resistance. Its high centre block to lug ratio provides excellent road ability and low soil damage, while the optimum land/sea ratio and dual angle block-lug improves soil cleaning, traction and wear.

GREEN XLR F77 is best suited for...

- Minimum soil compaction
- High traction capacity and low slippage
- ON/OFF traction and appearance owing to its shoulder buttress
- Enhanced mud removal and traction provided by the dual layer tie bar and mud-breaker

TECHNICAL DATA



TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension ± 2%		SLR	RC ± 2.5%	SRI	SPEED	LOAD CAPACITY (KG / TIRE)								
			Rec.	Alt.	(mm)	(mm)					(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
																			S.W.
22.5																			
500/60R22.5	155 D / 166 A8	TL	AG 16.00	15.00, 16.00, 17.00	503	1172	521	3592	550	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	1485	1775	2085	2380	2670	2965	3250	3530
											65	1630	1950	2290	2610	2930	3255	3565	3875
											50	1970	2360	2770	3160	3545	3940	4315	4689
											40	2225	2665	3130	3570	4005	4450	4875	5300
											25	2570	3080	3620	4125	4630	5145	5635	6123
											10	2930	3510	4120	4700	5275	5860	6415	6975
560/60R22.5	161 D / 172 A8	TL	AG 16.00	16.00, 17.00, AG 20	543	1244	549	3785	600	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	1770	2120	2490	2840	3185	3540	3875	4215
											65	1945	2325	2735	3115	3495	3885	4255	4625
											50	2350	2815	3305	3770	4230	4700	5150	5595
											40	2645	3170	3725	4245	4765	5290	5795	6300
											25	3070	3675	4320	4925	5525	6140	6725	7310
											10	3495	4185	4920	5610	6295	6995	7650	8325
600/50R22.5	159 D / 170 A8	TL	AG 20	...	611	1172	521	3592	550	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	1675	2005	2355	2685	3015	3350	3665	3985
											65	1840	2200	2585	2950	3310	3675	4025	4375
											50	2225	2665	3130	3565	4000	4445	4870	5295
											40	2520	3020	3545	4045	4535	5040	5520	6000
											25	2905	3475	4085	4660	5225	5805	6360	6915
											10	3310	3960	4655	5310	5955	6615	7245	7875
560/45R22.5	152 D / 163 A8	TL	AG 16.00	...	543	1076	484	3303	525	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	1360	1625	1910	2180	2445	2715	2975	3255
											65	1490	1785	2100	2395	2685	2980	3265	3550
											50	1805	2160	2540	2895	3245	3610	3950	4295
											40	2050	2450	2880	3285	3685	4095	4485	4875
											25	2355	2820	3315	3780	4240	4710	5160	5610
											10	2685	3215	3775	4305	4830	5365	5880	6390
26.5																			
600/55R26.5	165 D / 176 A8	TL	AG 20	...	611	1333	596	4092	625	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	1970	2360	2775	3160	3545	3940	4315	4690
											65	2165	2590	3045	3470	3895	4325	4740	5150
											50	2615	3135	3685	4200	4710	5235	5735	6030
											40	2980	3570	4195	4785	5370	5965	6530	7100
											25	3420	4095	4810	5485	6150	6833	7485	8135
											10	3895	4665	5480	6250	7010	7785	8530	9270
650/55R26.5	169 D / 180 A8	TL	AG 20	...	645	1389	600	4270	650	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	2220	2660	3125	3560	3995	4440	4860	5285
											65	2435	2915	3430	3910	4385	4870	5335	5800
											50	2950	3530	4150	4730	5305	5895	6455	7020
											40	3360	4025	4730	5390	6045	6720	7360	8000
											25	3850	4610	5415	6175	6930	7700	8430	9165
											10	4385	5250	6170	7035	7895	8770	9605	10440
710/50R26.5	170 D / 181 A8	TL	AG 24	AG 20	727	1383	615	4246	650	bar/kmph	1.2	1.6	2	2.4	2.8	3.2	3.6	4	
											70	2295	2750	3230	3685	4130	4590	5030	5465
											65	2520	3020	3545	4045	4535	5055	5520	6000
											50	3050	3650	4290	4895	5490	6100	6680	7260
											40	3465	4150	4875	5560	6235	6930	7590	8250
											25	3980	4770	5605	6390	7165	7965	8720	9480
											10	4535	5430	6385	7280	8165	9070	9935	10800

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. If any tire covered by this warranty is identified as unserviceable tire due to a material / workmanship /any other manufacturing defect, we will either repair the tire or make an allowance on purchase of new tire as per the current price of a new tire by the percentage of original tread worn off at the time of making the claim.

The cost of transportation, service, and sales tax already paid will be borne by the owner of the claimed tire. This limited warranty is made for the exclusive benefit of the tire owner actually using the product. No other warranty of liability, expressed or implied, is applicable to this limited warranty or to our products.

Business today is complex, ambiguous and uncertain – a little like life itself. To help you advance and attain your goals, you need something that is completely the opposite. GRI tires are robustly engineered and relentlessly tested to give you assured performance, so you can get a grip on things that really matter to you. Whatever your ambition, GRI will get you there.

DISTRIBUTOR: